

SECTION 4 ***COUPLERS***



Couplers

Poppet Couplers

ISO7241-1 A-Series



KQRP-F/M-A | Page 287

NV Faster Interchange



KQRP-F/M-NV | Page 287

ISO7241-1 A-Series
Connect Under Pressure



KQRP-F/M-A/NV CUP
Page 288

ISO7241-1 A Series Push
Pull



KQRP-F-PP | Page 288

ISO7241-1 B-Series



KQRP-F/M-B | Page 289

ISO7241-1B B-Series
(Carpet Cleaners)



KQRP-F/M-B-BRASS
Page 289

Agricultural Couplers

Ball Coupler



KQRB | Page 291

Ball Push Pull ISO7241-1
A-Series



KQRB-F-PP
Page 291

Tractor Rigid Mount
Breakaway



KQRP-F-JD-PP-SW
Page 291

PBR Interchange

PBR Interchange
Poppet Coupler



KQRP-F/M-PBR
Page 292

Nordic Interchange

Tema Interchange
Poppet



KQRT-F/M | Page 292

Tema Interchange
Connect Under Pressure



KQRT-F/M-E | Page 293

Flat Face

ISO16028 A-Series
High-Pressure



KQRF-F/M-UNO/BSP
Page 294

ISO16028 A-Series High Pressure
Connect Under Pressure



KQRF-M-UNO/CUP
Page 295

ISO16028 A-Series
High-Pressure Bulkhead



KQRF-F/M-ORFS BH/JIC BH |
Page 296

Screw Together

ISO14541 VD Poppet



KQRS-F/M-VD | Page 297

Faster VV Interchange



KQRS-F/M-VV | Page 298

Screw Together Flat Face

VEP Interchange



KQRS-F/M-FF-BSP
Page 299



TAIPAN

Couplers

Jacking

ISO14540 720 BAR



KQRJ-F/M-NPT
Page 301

700 BAR Flat Face



KQRJ-FF-F/M
Page 301

Coupler Accessories

Poppet Caps, Plugs & Seal Kits

ISO7241-1 A-Series
Caps & Plugs



KQRC-C/P-A
Page 289

NV Faster Interchange
Caps & Plugs



KQRC-C/P-NV
Page 290

Seal Kit



KQRP-A/NV-SK
Page 290

Caps & Plugs



KQRC-C/P/-PBR | Page 292

Seal Kits



KQRP-SK-PBR | Page 292

Nordic Interchange Caps, Plugs & Seal Kits

Caps & Plugs



KQRC-P/C-T | Page 293

Seal Kit



KQRT-SEALKIT
Page 293

Flat Face Caps, Plugs & Colour Rings

S016028 A-Series
High-Pressure Caps & Plugs



KQRC-C/P-FF
Page 296

Colour Coding Rings for
Flat Face Couplers



COLOUR RINGS
Page 297

Screw Together Caps, Plugs & Seal Kits

ISO14541
Caps & Plugs



KQRC-C-VD | Page 298

Faster Interchange VV
Caps & Plugs



KQRC-C-VV | Page 299

Screw Together Flat Face Plugs & Caps

Screw Together Flat
Face Caps & Plugs



KQRC-FF-S | Page 300

Jacking Caps & Plugs

ISO14541 700 BAR
Caps & Plugs



KQRC-C/P-J | Page 301

MORE PRODUCTS
COMING SOON



D.N.P.

Did you know that Taipan is Australia's largest supplier of D.N.P. products?

D.N.P. Industriale Srl, established in 1985, has been a prominent manufacturer of precision quick couplings for hydraulic systems. Renowned for their innovation, reliability, and exceptional products like push pull valves and special executions, D.N.P. has earned a leading position in the global quick coupling industry.

Taipan takes immense pride in offering D.N.P. products, as they are manufactured in-house in Italy with unwavering product monitoring, emphasising D.N.P.'s commitment to quality beyond the finished product. This unwavering dedication is why Taipan firmly believes in the superiority of D.N.P. products.



TAIPAN
Hydraulic Hose Systems

Poppet Couplers

Poppet Couplers

ISO7241-1 A Series

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Standard A-series seals are nitrile, back up rings are PTFE. Viton seals are available on request.

Interchanges with DNP PAV1, Stucchi, Faster ANV, Hansen HA, Parker 6600, 2000 and Aeroquip 5600, G5600, Ryco R81/82(1/2,3/4&1), Safeway S56.



SS = Stainless Steel

Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-04F-A	250	1/4 BSPP	12	6.3	11.85
KQRP-04M-A	250	1/4 BSPP	12	6.3	11.85
KQRP-06F-A	250	3/8 BSPP	23	10.0	17.30
KQRP-06M-A	250	3/8 BSPP	23	10.0	17.30
KQRP-08F-A/NV	250	1/2 BSPP	45	12.5	20.55
KQRP-08F-A/NV-SS	300	1/2 BSPP	45	12.5	20.55
KQRP-08F-M22	250	M22 X 1.5	45	12.5	20.55
KQRP-08M-7/8UNO	250	7/8 UNO	45	12.5	20.55
KQRP-08M-A/NV	250	1/2 BSPP	45	12.5	20.55
KQRP-08M-A/NV-3/4UNO	250	3/4 UNO	45	12.5	20.55
KQRP-08M-A/NV-SS	300	1/2 BSPP	45	12.5	20.55
KQRP-08M-M22	250	M22 X 1.5	45	12.5	20.55
KQRP-12F-A	250	3/4 BSPP	106	20.0	29.10
KQRP-12M-A	250	3/4 BSPP	106	20.0	29.10
KQRP-16F-A	200	1 BSPP	189	25.0	34.35
KQRP-16M-A	200	1 BSPP	189	25.0	34.35
KQRP-20F-A	200	1 1/4 BSPP	288	31.5	45.00
KQRP-20M-A	200	1 1/4 BSPP	288	31.5	45.00
KQRP-24F-A	60	1 1/2 BSPP	379	40.0	55.00
KQRP-24M-A	60	1 1/2 BSPP	379	40.0	55.00

Poppet Couplers

NV Faster Interchange

Interchanges with DNP PDV1, Parker 4000 series & Faster NV series.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-04F-NV	400	1/4 BSPP	12	6.3	14.20
KQRP-04M-NV	400	1/4 BSPP	12	6.3	14.20
KQRP-06F-NV	350	3/8 BSPP	23	10.0	19.00
KQRP-06M-NV	350	3/8 BSPP	23	10.0	19.00
KQRP-08F-A/NV	250	1/2 BSPP	45	12.5	20.55
KQRP-08F-M22	250	M22 X 1.5	45	12.5	20.55

Continued on following page...

Can't find what you're looking for?

1300 654 782

Poppet Couplers

Poppet Couplers

NV Faster Interchange *Continued...*

Interchanges with DNP PDV1, Parker 4000 series & Faster NV series.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-08M-7/8UNO	250	7/8 UNO	45	12.5	20.55
KQRP-08M-A/NV	250	1/2 BSPP	45	12.5	20.55
KQRP-08M-A/NV-3/4UNO	250	3/4 UNO	45	12.5	20.55
KQRP-08M-M22	250	M22 X 1.5	45	12.5	20.55
KQRP-12F-NV	250	3/4 BSPP	106	20.0	28.00
KQRP-12M-NV	250	3/4 BSPP	106	20.0	28.00
KQRP-16F-NV	250	1 BSPP	189	25.0	31.30
KQRP-16M-NV	250	1 BSPP	189	25.0	31.30

Poppet Couplers

ISO7241-1 A-Series Connect Under Pressure

Interchanges with DNP PDV1, Parker 4000 series & Faster NV series.
CUP = Connect under pressure (Residual Only).



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-08F-A/NV-CUP	250	1/2 BSPP	45	12.5	20.55
KQRP-08M-A/NV-CUP	250	1/2 BSPP	45	12.5	20.55

Poppet Couplers

ISO7241-1 A-Series Push Pull

Interchanges with DNP PPS1, PPV3, PPV1, Ryco R91 & R86, Stucchi 1RS/L.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-08F-A/NV-3/4UNO-PP	250	3/4 UNO	45	12.5	20.55
KQRP-08F-PP	250	1/2 BSPP	45	12.5	20.55
KQRP-08F-7/8UNO-PP	250	7/8 UNO	45	12.5	20.55



Poppet Couplers

Poppet Couplers

ISO7241-1 B Series

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Standard seals are nitrile, back up rings are PTFE. Viton seals are available on request. Interchanges with DNP PBV1, Faster HNV, Hansen HK, Parker 60 series - H, Aeroquip 60B/F6600 and Safeway S10.



SS = Stainless Steel

Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-06F-B	250	3/8 BSPP	23	10.0	19.10
KQRP-06M-B	250	3/8 BSPP	23	10.0	19.10
KQRP-06F-B-SS	350	3/8 BSPP	23	10.0	19.10
KQRP-06M-B-SS	350	3/8 BSPP	23	10.0	19.10
KQRP-08F-B	250	1/2 BSPP	45	12.5	23.55
KQRP-08M-B	250	1/2 BSPP	45	12.5	23.55
KQRP-12F-B	250	3/4 BSPP	106	20.0	31.45
KQRP-12M-B	250	3/4 BSPP	106	20.0	31.45
KQRP-16F-B	200	1 BSPP	189	25.0	37.77
KQRP-16M-B	200	1 BSPP	189	25.0	37.77

Poppet Couplers

ISO7241-1 B Series (Carpet Cleaners)

Manufactured from brass. Standard seals are nitrile, back up rings are PTFE. Viton seals are available on request. Interchanges with DNP PBV1, Faster HNV, Hansen HK, Parker 60 series - H, Aeroquip 60B/F6600 and Safeway S10.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ϕ
KQRP-04F-B-BRASS	200	1/4 BSPP	12	6.3	14.20
KQRP-04M-B-BRASS	200	1/4 BSPP	12	6.3	14.20

Poppet Caps, Plugs & Seal Kits

Poppet Caps, Plugs & Seal Kits

ISO7241-1 A-Series Caps & Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-04C-A	1/4	CAP	MALE	PVC
KQRC-04P-A	1/4	PLUG	FEMALE	PVC
KQRC-06C-A	3/8	CAP	MALE	PVC
KQRC-06P-A	3/8	PLUG	FEMALE	PVC
KQRC-08C-A/NV-BLACK	1/2	CAP	MALE	PVC
KQRC-08C-A/NV-BLUE	1/2	CAP	MALE	PVC
KQRC-08C-A/NV-GREEN	1/2	CAP	MALE	PVC

Continued on following page...

Can't find what you're looking for?

1300 654 782

Poppet Caps, Plugs & Seal Kits

Poppet Caps, Plugs & Seal Kits

ISO7241-1 A-Series Caps & Plugs *Continued...*



ADC

Part Number	Size	Type	Fits Gender	Material
KQRC-08C-A/NV-YELLOW	1/2	CAP	MALE	PVC
KQRC-08C-A/NV-RED	1/2	CAP	MALE	PVC
KQRC-08C-A/NV ADC	1/2	CAP	FEMALE	PVC
KQRC-08P-A/NV-BLACK	1/2	PLUG	FEMALE	PVC
KQRC-08P-A/NV-BLU	1/2	PLUG	FEMALE	PVC
KQRC-08P-A/NV-GREEN	1/2	PLUG	FEMALE	PVC
KQRC-08P-A/NV-YELLOW	1/2	PLUG	FEMALE	PVC
KQRC-08P-A/NV-RED	1/2	PLUG	FEMALE	PVC
KQRC-12C-A- RED	3/4	CAP	MALE	PVC
KQRC-12C-A-BLACK	3/4	CAP	MALE	PVC
KQRC-12C-A-GREY	3/4	CAP	MALE	PVC
KQRC-12P-A-RED	3/4	PLUG	FEMALE	PVC
KQRC-12P-A-BLACK	3/4	PLUG	FEMALE	PVC
KQRC-12P-A-GREY	3/4	PLUG	FEMALE	PVC
KQRC-16C-A	1	CAP	MALE	PVC
KQRC-16P-A	1	PLUG	FEMALE	PVC

Poppet Caps, Plugs & Seal Kits

NV Faster Interchange Caps & Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-04C-NV	1/4	CAP	MALE	PVC
KQRC-04P-NV	1/4	PLUG	FEMALE	PVC
KQRC-06C-NV	3/8	CAP	MALE	PVC
KQRC-06P-NV	3/8	PLUG	FEMALE	PVC
KQRC-12C-NV	3/4	CAP	MALE	PVC
KQRC-12P-NV	3/4	PLUG	FEMALE	PVC
KQRC-16C-NV	1	CAP	MALE	PVC
KQRC-16P-NV	1	PLUG	FEMALE	PVC

Poppet Caps, Plugs & Seal Kits

A/NV Series Seal Kits



Part Number	Size	Type	Fits Gender	Series
KQRP-08F-A/NV-SK	1/2	SEAL KIT	FEMALE	A/NV SERIES
KQRP-12F-A-SK	3/4	SEAL KIT	FEMALE	A SERIES
KQRP-16F-A-SK	1	SEAL KIT	FEMALE	A SERIES
KQRP-08F-A/NV-SK	1/2	SEAL KIT	FEMALE	A/NV SERIES
KQRP-12F-NV-SK	3/4	SEAL KIT	FEMALE	NV SERIES
KQRP-16F-NV-SK	1	SEAL KIT	FEMALE	NV SERIES



Agricultural

Agricultural

Ball Coupler

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Standard seals are nitrile, back up rings are PTFE. Viton seals are available on request.

Interchanges with DNP PPS1, Stucchi, IR (Ball) series, Parker 4000.

* Fixed Ball (Poppet type with seal).



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRB-04F	300	1/4 BSPP	12	6.3	14.20
KQRB-04M	300	1/4 BSPP	12	6.3	14.20
KQRB-06F	250	3/8 BSPP	23	10	19.00
KQRB-06M	250	3/8 BSPP	23	10	19.00
KQRB-08F	200	1/2 BSPP	30	12.5	20.55
KQRB-08M	200	1/2 BSPP	30	12.5	20.55
KQRB-08M-GH*	200	1/2 BSPP	30	12.5	20.55
KQRB-12F	200	3/4 BSPP	60	19	27.93
KQRB-12M	200	3/4 BSPP	60	19	27.93

Agricultural

Ball Push Pull ISO7241-1 Series-A

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Standard seals are nitrile, back up rings are PTFE. Viton seals are available on request.

Interchanges with DNP PPS1, Stucchi, IR (Ball) series, Parker 4000.

* Fixed Ball (Poppet type with seal).



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRB-08F-PP	200	1/2 BSPP	30	12.5	20.55
KQRB-08F-PP-GH*	200	1/2 BSPP	30	12.5	20.55

Agricultural

Tractor Rigid Mount Breakaway Coupler

Interchanges with Inteva 1077 series ISO 7421-A Faster 3CFPV, 4SRP, Parker RSD.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size
KQRP-08F-JD-PP-SW	275	1/2 BSPP	90	12.5

PBR Interchange

PBR Interchange

Poppet Coupler

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Standard seals are nitrile, back up rings are PTFE. Viton seals are available on request.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRP-16F-PBR	300	1 BSPP	200	25.0	38.00
KQRP-16M-PBR	300	1 BSPP	200	25.0	38.00

PBR Interchange


PBR Caps & Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-16C-PBR	1	CAP	MALE	PVC
KQRC-16P-PBR	1	PLUG	FEMALE	PVC

PBR Interchange

PBR Seal Kits



Part Number	Size	Type	Fits Gender
KQRP-16SK-PBR	1	SEAL KIT	FEMALE

Nordic Interchange

Nordic Interchange

Poppet

Manufactured from zinc plated carbon steel. Hardened ball contact areas. Double O'ring and backup for extra sealing capacity. Interchanges with Parker Tema T and H series, DNP PTVI, Stucchi IRC series and CEJN 525.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRT-04F	400	1/4 BSPP	12	6.3	11.95
KQRT-04M	400	1/4 BSPP	12	6.3	11.95
KQRT-06F	370	3/8 BSPP	45	10.0	20.00
KQRT-06M	370	3/8 BSPP	45	10.0	20.00
KQRT-08F	350	1/2 BSPP	90	12.5	24.80
KQRT-08M	350	1/2 BSPP	90	12.5	24.80
KQRT-12F	300	3/4 BSPP	212	19.0	32.70
KQRT-12M	300	3/4 BSPP	212	19.0	32.70
KQRT-16F	300	1 BSPP	380	25.0	40.90
KQRT-16M	300	1 BSPP	380	25.0	40.90



Nordic Interchange

Nordic Interchange

Connect Under Pressure

Interchanges with Parker Tema T series, DNP PTKI, Stucchi IRC-PC series and CEJN 525.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRT-08F-E	300	1/2 BSPP	90	12.5	24.8
KQRT-08M-E	300	1/2 BSPP	90	12.5	24.8
KQRT-12F-E	300	3/4 BSPP	212	19.0	32.70
KQRT-12M-E	300	3/4 BSPP	212	19.0	32.70
KQRT-16F-E	300	1 BSPP	380	25.0	40.90
KQRT-16M-E	300	1 BSPP	380	25.0	40.90

Nordic Interchange


Caps & Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-06P-B/TEMA	3/8	PLUG	FEMALE	PVC
KQRC-06C-B/TEMA	3/8	CAP	MALE	PVC
KQRC-08C-B/TEMA	1/2	CAP	MALE	PVC
KQRC-08P-B/TEMA	1/2	PLUG	FEMALE	PVC
KQRC-12C-T	3/4	CAP	MALE	PVC
KQRC-12P-T	3/4	PLUG	FEMALE	PVC
KQRC-16C-T	1	CAP	MALE	PVC
KQRC-16P-T	1	PLUG	FEMALE	PVC

Nordic Interchange

Seal Kits



Part Number	Size	Type	Fits Gender
KQRT-08-SEALKIT	1/2	SEAL KIT	FEMALE
KQRT-12-SEALKIT	3/4	SEAL KIT	FEMALE
KQRT-16-SEALKIT	1	SEAL KIT	FEMALE

Flat Face

Flat Face

ISO16028 A-Series High-Pressure

Flat interface allows easy cleaning. Low spill, low air inclusion. Safety locking sleeve. 12-20 locking balls for optimum life. 3/8 sizes meets HTMA interchange dimensions.
Interchanges with DNP PLT4, Stucchi FITG/A series, Faster 2FFI (up to 1/2) & FFN38, Parker FF (3/8 only), Hansen QA, Ryco R110-06/08, Safeway FF49, Aeroquip FD89/FD49.

EXAMPLE: KQRF 08 10 M or F 5/8ORFS BH
Flat Face ISO Body Size Thread Dash Size Male/Female Thread Type If it is a bulkhead fitting



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter Ø
KQRF-02-02AF	500	1/8 BSPP	3	5.0	13.60
KQRF-02-02AM	500	1/8 BSPP	3	5.0	13.60
KQRF-04-04F	400	1/4 BSPP	12	6.3	16.20
KQRF-04-04M	400	1/4 BSPP	12	6.3	16.20
KQRF-06-06F	350	3/8 BSPP	23	10.0	19.80
KQRF-06-06M	350	3/8 BSPP	23	10.0	19.80
KQRF-06-08F	350	1/2 BSPP	23	10.0	19.80
KQRF-06-08F-UNO	350	3/4 UNO	23	10.0	19.80
KQRF-06-08M	350	1/2 BSPP	23	10.0	19.80
KQRF-06-08M-UNO	350	3/4 UNO	23	10.0	19.80
KQRF-08-08AF	350	1/2 BSPP	45	12.5	24.60
KQRF-08-08AM	350	1/2 BSPP	45	12.5	24.60
KQRF-08-10F UNO	350	7/8 UNO	45	12.5	24.60
KQRF-08-10M UNO	350	7/8 UNO	45	12.5	24.60
KQRF-08-12F	350	3/4 BSPP	45	12.5	24.60
KQRF-08-12F UNO	350	1 1/16 UNO	45	12.5	24.60
KQRF-08-12M	350	3/4 BSPP	45	12.5	24.60
KQRF-08-12M UNO	350	1 1/16 UNO	45	12.5	24.60
KQRF-10-12F-BSP	350	3/4 BSPP	74	16.0	27.00
KQRF-10-12F-UNO	350	1 1/16 UNO	74	16.0	27.00
KQRF-10-12M-BSP	350	3/4 BSPP	74	16.0	27.00
KQRF-10-12M-UNO	350	1 1/16 UNO	74	16.0	27.00
KQRF-12-12F BSP	350	3/4 BSPP	100	19.0	30.00
KQRF-12-12F UNO	350	1 1/16 UNO	100	19.0	30.00
KQRF-12-12M BSP	350	3/4 BSPP	100	19.0	30.00
KQRF-12-12M-UNO	350	1 1/16 UNO	100	19.0	30.00
KQRF-12-16F	350	1 BSPP	100	19.0	30.00
KQRF-12-16F-UNO	350	1 5/16 UNO	100	19.0	30.00
KQRF-12-16M	350	1 BSPP	100	19.0	30.00



Flat Face

Flat Face

ISO16028 A-Series High-Pressure *Continued...*

Flat interface allows easy cleaning. Low spill, low air inclusion. Safety locking sleeve. 12-20 locking balls for optimum life. 3/8 sizes meets HTMA interchange dimensions.
Interchanges with DNP PLT4, Stucchi FITG/A series, Faster 2FFI (up to 1/2) & FFN38, Parker FF (3/8 only), Hansen QA, Ryco R110-06/08, Safeway FF49, Aeroquip FD89/FD49.

EXAMPLE: KQRF 08 10 M or F 5/8ORFS BH
Flat Face ISO Body Size Thread Dash Size Male/Female Thread Type If it is a bulkhead fitting



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter Ø
KQRF-12-16M-UNO	350	1 5/16 UNO	100	19.0	30.00
KQRF-16-16F BSP	350	1 BSPP	189	25.0	36.00
KQRF-16-16M BSP	350	1 BSPP	189	25.0	36.00
KQRF-16-20F	350	1 1/4 BSPP	189	25.0	36.00
KQRF-16-20M	350	1 1/4 BSPP	189	25.0	36.00
KQRF-20-20F	250	1 1/4 BSPP	260	31.5	44.00
KQRF-20-20M	250	1 1/4 BSPP	260	31.5	44.00
KQRF-24-24F	250	1 1/2 BSPP	379	40.0	57.00
KQRF-24-24M	250	1 1/2 BSPP	379	40.0	57.00

Flat Face

ISO16028 A-Series High-Pressure Connect Under Pressure

Flat interface allows easy cleaning. Low spill, low air inclusion. Safety locking sleeve. 12-20 locking balls for optimum life. 3/8 sizes meets HTMA interchange dimensions.
Interchanges with DNP PLT4, Stucchi FIRG/A series, Faster 2FFI (up to 1/2) & FFN38, Parker FF (3/8 only), Hansen QA, Ryco R110-06/08, Safeway FF49, Aeroquip FD89/FD49.
CUP = Connect under pressure.

EXAMPLE: KQRF 08 10 M or F 5/8ORFS BH
Flat Face ISO Body Size Thread Dash Size Male/Female Thread Type If it is a bulkhead fitting



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter Ø
KQRF-08-08M-CUP	350	1/2 BSPP	45	12.5	24.50
KQRF-08-10M UNO-CUP	350	7/8 UNO	45	12.5	24.50
KQRF-08-12M UNO-CUP	350	1 1/16 UNO	45	12.5	24.50
KQRF-12-12M BSP-CUP	350	3/4 BSPP	100	19	30.00

Continued on following page...

Can't find what you're looking for?

1300 654 782

295

Email: sales@taipan.com.au
Fax 07 5428 1311

Flat Face

Flat Face

ISO16028 A-Series High-Pressure Bulkhead

Flat interface allows easy cleaning. Low spill, low air inclusion. Safety locking sleeve. 12-20 locking balls for optimum life. 3/8 sizes meets HTMA interchange dimensions.

Interchanges with DNP PLT4, Stucchi FIRG/A series, Faster 2FFI (up to 1/2) & FFN38, Parker FF (3/8 only), Hansen QA, Ryco R110-06/08, Safeway FF49, Aeroquip FD89/FD49.

EXAMPLE: KQRF 08 10 M or F 5/8ORFS BH
Flat Face ISO Body Size Thread Dash Size Male/Female Thread Type If it is a bulkhead fitting



Part Number	Pressure Rating/ BAR	Male Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRF-08-10F-5/8ORFSBH	350	1 ORFS BH	45	12.5	24.60
KQRF-08-10F-7/8JICBH	350	7/8 JIC BH	45	12.5	24.60
KQRF-08-10M-5/8ORFSBH	350	1 ORFS BH	45	12.5	24.60
KQRF-08-10M-7/8JICBH	350	7/8 JIC BH	45	12.5	24.60

Flat Face Caps & Plugs

Flat Face Caps & Plugs

ISO16028 A-Series High-Pressure Caps & Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-04C-FF	1/4	CAP	MALE	PVC
KQRC-04P-FF	1/4	PLUG	FEMALE	PVC
KQRC-06C-FF	3/8	CAP	MALE	PVC
KQRC-06P-FF	3/8	PLUG	FEMALE	PVC
KQRC-08C-FF	1/2	CAP	MALE	PVC
KQRC-08P-FF	1/2	PLUG	FEMALE	PVC
KQRC-10C-FF-AL	5/8	CAP	MALE	ALUMINIUM
KQRC-10P-FF-AL	5/8	PLUG	FEMALE	ALUMINIUM
KQRC-12C-FF	3/4	CAP	MALE	PVC
KQRC-12P-FF	3/4	PLUG	FEMALE	PVC
KQRC-16C-FF	1	CAP	MALE	PVC
KQRC-16P-FF	1	PLUG	FEMALE	PVC



Flat Face Colour Rings

Flat Face Colour Rings

Colour Rings

Ideal for colour coding couplers to match male to female.
Other sizes available on request.



Part Number	Description	Size	Colour
KQRCR-08F-BLUE		1/2	BLUE
KQRCR-08F-GREEN		1/2	GREEN
KQRCR-08F-GREY		1/2	GREY
KQRCR-08F-ORANGE		1/2	ORANGE
KQRCR-08F-RED		1/2	RED
KQRCR-08F-VIOLET		1/2	VIOLET
KQRCR-08F-WHITE		1/2	WHITE
KQRCR-08F-YELLOW		1/2	YELLOW
KQRCR-08M-BLUE		1/2	BLUE
KQRCR-08M-GREEN		1/2	GREEN
KQRCR-08M-GREY		1/2	GREY
KQRCR-08M-ORANGE		1/2	ORANGE
KQRCR-08M-RED		1/2	RED
KQRCR-08M-VIOLET		1/2	VIOLET
KQRCR-08M-WHITE		1/2	WHITE
KQRCR-08M-YELLOW		1/2	YELLOW
KQRCR-08M-TOOL		1/2	N/A

Screw Together

Screw Together

ISO14541 VD Poppet

Interchanges with DNP PVV3, Stucchi VD series, Faster CVV, Parker QHPA & Ryco R120.

EXAMPLE: KQRS 08 10 M or F
Flat Face ISO Body Size Thread Dash Size Male/Female



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRS-04F-VD	450	1/4 BSPP	12	6.3	
KQRS-04M-VD	450	1/4 BSPP	12	6.3	24.00
KQRS-06F-VD	400	3/8 BSPP	23	10.0	
KQRS-06M-VD	400	3/8 BSPP	23	10.0	28.00
KQRS-08F-VD	400	1/2 BSPP	45	12.5	
KQRS-08M-VD	400	1/2 BSPP	45	12.5	36.00
KQRS-12F-VD	300	3/4 BSPP	106	19.0	

Can't find what you're looking for?

1300 654 782

Screw Together

Screw Together

ISO14541 VD Poppet *Continued...*

Interchanges with DNP PVV3, Stucchi VD series, Faster CVV, Parker QHPA & Ryco R120.

EXAMPLE: KQRS Flat Face 08 ISO Body Size 10 Thread Dash Size M or F Male/Female



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRS-12M-VD	300	3/4 BSPP	106	19.0	42.00
KQRS-16-12F-VD	300	3/4 BSPP	189	25.0	
KQRS-16-12M-VD	300	3/4 BSPP	189	25.0	48.00
KQRS-16F-VD	300	1 BSPP	189	25.0	
KQRS-16M-VD	300	1 BSPP	189	25.0	48.00

Screw Together

Faster VV Interchange

Interchanges with DNP-VDVI and Faster VV series.



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRS-06F-VV	300	3/8 BSPP	23	10.0	
KQRS-06M-VV	300	3/8 BSPP	23	10.0	19.0
KQRS-08F-VV	300	1/2 BSPP	45	12.5	
KQRS-08M-VV	300	1/2 BSPP	45	12.5	20.50
KQRS-12F-VV	250	3/4 BSPP	106	19.0	
KQRS-12M-VV	250	3/4 BSPP	106	19.0	27.90
KQRS-16F-VV	230	1 BSPP	189	25.0	
KQRS-16M-VV	230	1 BSPP	189	25.0	31.30

Screw Together Caps, Plugs & Seal Kits

Screw Together Caps, Plugs & Seal Kits

ISO14541 Caps, Plugs & Seal Kits



Part Number	Size	Type	Fits Gender	Material
KQRC-06C-VD	3/8	CAP	MALE	PVC
KQRC-06P-VD	3/8	PLUG	FEMALE	PVC
KQRC-08C-VD	1/2	CAP	MALE	PVC
KQRC-08C-VD-AL	1/2	CAP	MALE	ALUMINIUM
KQRC-08P-VD	1/2	PLUG	FEMALE	PVC
KQRC-08P-VD-AL	1/2	PLUG	FEMALE	ALUMINIUM
KQRC-12P-VD	3/4	PLUG	FEMALE	PVC
KQRC-12P-VD-AL	3/4	PLUG	FEMALE	ALUMINIUM

Continued on following page...

Screw Together Caps, Plugs & Seal Kits

Screw Together Caps, Plugs & Seal Kits



ISO14541 Caps, Plugs & Seal Kits *Continued...*

Part Number	Size	Type	Fits Gender	Material
KQRC-12C-VD	3/4	CAP	MALE	PVC
KQRC-12C-VD-AL	3/4	CAP	MALE	ALUMINIUM
KQRC-16C-VD	1	CAP	MALE	PVC
KQRC-16P-VD	1	PLUG	FEMALE	PVC
KQRS-16F-VD-SEALKIT	1	SEAL KIT	FEMALE	

Screw Together Caps, Plugs & Seal Kits



VV Caps & Plugs

Part Number	Size	Type	Fits Gender	Material
KQRC-08C-VV-AL	1/2	CAP	MALE	ALUMINIUM
KQRC-08P-VV-AL	1/2	PLUG	FEMALE	ALUMINIUM
KQRC-12C-VV-AL	3/4	CAP	MALE	ALUMINIUM
KQRC-12P-VV-AL	3/4	PLUG	FEMALE	ALUMINIUM
KQRC-16C-VV-AL	1	CAP	MALE	ALUMINIUM
KQRC-16P-VV-AL	1	PLUG	FEMALE	ALUMINIUM

Screw Together Flat Face

Screw Together Flat Face

VEP Interchange

Interchanges with DNP PVT4 (-20) and PST4, Stucchi VEP series, Aeroquip FD96.

EXAMPLE: KQRS 08 10 M or F Flat Face BSP
Flat Face ISO Body Size Thread Dash Size Male/Female Coupler Type Thread Type



NB: Exclusive profile for -20

Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRS-08-08F-FF-BSP	350	1/2 BSPP	45	12.5	24.50
KQRS-08-08M-FF-BSP	350	1/2 BSPP	45	12.5	24.50
KQRS-10-12F-FF-BSP	350	3/4 BSPP	74	16.0	27.00
KQRS-10-12M-FF-BSP	350	3/4 BSPP	74	16.0	27.00
KQRS-12-16F-FF-BSP	350	1 BSPP	100	19.0	29.90
KQRS-12-16M-FF-BSP	350	1 BSPP	100	19.0	29.90
KQRS-16-16F-FF-BSP	350	1 BSPP	189	25.0	36.00
KQRS-16-16M-FF-BSP	350	1 BSPP	189	25.0	36.00
KQRS-16-20F-FF-BSP	350	1 1/4 BSPP	189	25.0	36.00

Continued on following page...

Can't find what you're looking for?

1300 654 782

Screw Together Flat Face

Screw Together Flat Face

VEP Interchange *Continued...*

Interchanges with DNP PVT4 (-20) and PST4, Stucchi VEP series, Aeroquip FD96.

EXAMPLE:

KQRS
Flat Face

08
ISO Body Size

10
Thread Dash Size

M or F
Male/Female

Flat Face
Coupler Type

BSP
Thread Type



Part Number	Pressure Rating/ BAR	Female Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRS-20-20F-FF-BSP	350	1 1/4 BSPP	288	31.5	44.00
KQRS-20-20M-FF-BSP	350	1 1/4 BSPP	288	31.5	44.00
KQRS-24-24F-FF-BSP	300	1 1/2 BSPP	379	40.0	56.90
KQRS-24-24M-FF-BSP	300	1 1/2 BSPP	379	40.0	56.90

NB: Exclusive profile for -20

Screw Together Flat Face Caps & Plugs

Screw Together Flat Face Caps & Plugs

VEP Interchange



NB: Exclusive profile for -20

Part Number	Size	Type	Fits Gender	Material
KQRC-08C-FFS-AL	1/2	CAP	MALE	ALUMINIUM
KQRC-08P-FFS-AL	1/2	PLUG	FEMALE	ALUMINIUM
KQRC-10C-FFS-AL	5/8	CAP	MALE	ALUMINIUM
KQRC-10P-FFS-AL	5/8	PLUG	FEMALE	ALUMINIUM
KQRC-12C-FFS-AL	3/4	CAP	MALE	ALUMINIUM
KQRC-12P-FFS-AL	3/4	PLUG	FEMALE	ALUMINIUM
KQRC-16C-FFS-AL	1	CAP	MALE	ALUMINIUM
KQRC-16P-FFS-AL	1	PLUG	FEMALE	ALUMINIUM
KQRC-20C-FFS-AL	1 1/4	CAP	MALE	ALUMINIUM
KQRC-20P-FFS-AL	1 1/4	PLUG	FEMALE	ALUMINIUM

Continued on following page...



TAIPAN

Jacking

Jacking

ISO14540 720 BAR

Designed for high pressure hydraulic applications such as jacking systems.



BALL



POPPET

Part Number	Pressure Rating/ BAR	Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRJ-04F	720	1/4 NPTM	5	6.3	15.90
KQRJ-04M	720	1/4 NPTF	5	6.3	15.90
KQRJ-06F-NPTF	720	3/8 NPTF	9	10.0	19.00
KQRJ-06F-NPTM	720	3/8 NPTM	9	10.0	19.00
KQRJ-06M-NPTF	720	3/8 NPTF	9	10.0	19.00
KQRJP-06F-NPTF	720	3/8 NPTF	9	10.0	19.00
KQRJP-06M-NPTF	720	3/8 NPTF	9	10.0	19.00

Jacking

700 BAR Flat Face

Interchanges with DNP PLT7 and Stucchi HP.



Part Number	Pressure Rating/ BAR	Thread	Rated Flow Rate L/M	ISO Coupler Body Size	Male Tip Diameter ø
KQRJFF-04-06F-NPT	700	3/8 NPTF	12	6.3	16.60
KQRJFF-04-06M-NPT	700	3/8 NPTF	12	6.3	16.60

Jacking Caps & Plugs

Jacking Caps & Plugs

ISO14541 700 BAR Caps and Plugs



Part Number	Size	Type	Fits Gender	Material
KQRC-04C-J	1/4	CAP	MALE	STEEL
KQRC-04P-J	1/4	PLUG	FEMALE	STEEL
KQRC-06P/C-J	3/8	CAP + PLUG	UNI-SEX	PVC



SOCIALS

Ever wondered what happens behind the scenes?

Our socials are loaded with awesome content to make your day just that bit brighter!

From crazy Christmas videos to warehouse shenanigans and everything in between, we're always up to something cool in our branches that you'll be sure to want in on.

Plus, did we mention we give away prizes monthly? Who doesn't want something for nothing!

Want in? All you need to do is like us and we'll provide the free entertainment!

Head to:

f **taipanptyltd**
in **taipan-hose**
@ **taipanptyltd**



TAIPAN
Hydraulic Hose Systems



We are proudly Australian
owned and operated



Taipan Hydraulics has been in
operation for over 30 years

2500+
ADAPTORS

6500+
PRODUCTS

We stock a massive range of
quality hydraulic hoses and
adaptors



TAIPAN
Hydraulic Hose Systems



TAIPAN

Hydraulic Hose Systems

CABOOLTURE

11-13 Lear Jet Drive
Caboolture, QLD 4510
Ph: 07 5428 1211
Fax: 07 5428 1311

ROCKLEA

41 Shettleston Street
Rocklea, QLD 4106
Ph: 07 3274 3433
Fax: 07 3274 3477

ADELAIDE

Warehouse 1
Lot 552 Wilkins Road
Wingfield, SA 5013
Ph: 08 8448 3969

MELBOURNE

23 Endeavour Way
Sunshine West, Vic 3020
Ph: 03 9109 2109
Fax: 03 8317 9049

PERTH

3 Mordaunt Cct
Canning Vale, WA 6155
Ph: 08 9456 5448
Fax: 08 9256 1242

CONTACT US 1300 654 782

taipan.com.au