

# 100R1PWH **ACCESSORY HOSE**

## WATERBLAST HOSE

This single-wire, braided hydraulic hose is designed for professional pressure cleaning applications. Its outer cover enhances detergent, weather, ozone and abrasion resistance. Meets or exceeds EN ISO 7751 standards.



## TECHNICAL DETAILS

### CONSTRUCTION

**Inner Tube:** Synthetic rubber  
**Reinforcement:** One braid of high-tensile steel wire  
**Outer Cover:** Detergent, ozone, weather, and abrasion resistant synthetic rubber, blue or grey

### APPLICATION

Professional pressure cleaning applications.

### SPECIFICATIONS

**Standards:** Meets or exceeds ISO7751  
**Temperature Range:** -10°C - 155°C  
**Hose Tails:** K series

Part Number	Size (in)	ID (mm)	OD (mm)	Working PSI	Min. Burst Pressure (PSI)	Min. Bend Radius (mm)	Reel Length (m)	Weight (kg/m)
100R1PWH-04 (BL*)	1/4	6.6	12	4000	12000	35	Random	0.18
100R1PWH-06 (G**)	3/8	9.9	15.1	4000	12000	65	Random	0.26

\*BL = Blue Cover

\*\*G = Grey Cover



**TAIPAN**

Email: [sales@taipan.com.au](mailto:sales@taipan.com.au)  
Fax: 07 5428 1311

**CONTACT US 1300 654 782**  
[www.taipan.com.au](http://www.taipan.com.au)