

OM-32-4 MOBILE CRIMPER



FEATURES

- Up to 2" 4-wire spiral hose
- Compact design
- Available in 12v or 24v

CONTROL

Dial Vernier

WEIGHT

Machine (kg) 140

TECHNICAL DATA

| | |
|-----------------------------|------------------------|
| Max. crimping diameter (mm) | 8.0-82.0 |
| Max. opening (without dies) | 124mm |
| Max. crimping force (kN) | 2517 |
| Max. hose size | 3/16" - 2" (4 wire) |
| Motor options | 12v DC |
| | 24v DC |
| Max. cycle time | 5s closing, 5s opening |

DIE SETS

| Die Set No. | L (mm) | Crimp Range (mm) | Max. ferrule Dia. |
|-------------|--------|------------------|-------------------|
| 08* | 40 | 8.0-9.9 | 20 |
| 10* | 40 | 10.0-11.9 | 22 |
| 12* | 40 | 12.0-13.9 | 24 |
| 14* | 40 | 14.0-15.9 | 26 |
| 16 | 40 | 16.0-18.9 | 28 |
| 19 | 40 | 19.0-21.9 | 31 |
| 22 | 50 | 22.0-25.9 | 34 |
| 26 | 50 | 26.0-27.9 | 38 |
| 28 | 50 | 28.0-29.9 | 40 |
| 30 | 60 | 30.0-33.9 | 42 |
| 34 | 70 | 34.0-39.9 | 46 |
| 40 | 70 | 40.0-45.9 | 52 |
| 46 | 80 | 46.0-79.9 | 58 |
| 52 | 80 | 52.0-57.9 | 64 |
| 58 | 80 | 58.0-63.9 | 70 |
| 64 | 80 | 64.0-69.9 | 66 |
| 70 | 95 | 70.0-82.0 | 82 |

*Optional die sets available