

OM-32-6 QC **CRIMPER**



FEATURES

- Up to 2" 6-wire spiral hose
- Quick Change Tool included
- Die rack

CONTROL

Dial Vernier

WEIGHT

Machine (kg) 320

DIE SETS

Die Set No.	L (mm)	Crimp Range (mm)	Max. ferrule Dia.
0605*	40	6.0-7.9	18
0805*	40	8.0-9.9	20
10*	40	10.0-12.9	22
13*	40	13.0-15.9	25
1605	50	16.0-18.9	28
19	40	19.0-21.0	31
21	50	21.0-21.9	33
24	50	24.0-25.9	36
26	50	26.0-27.9	38
28	50	28.0-30.9	40
31	60	31.0-33.9	43
34	70	34.0-39.9	47
40	85	40.0-43.9	52
44	80	44.0-49.9	56
50	80	50.0-49.9	62
54.5	100	54.9-57.9	66.5
58	105	58.0-61.9	70
62	110	62.0-69.9	74
70	110	70.0-76.9	82
77	120	77.0-89.9	89

TECHNICAL DATA

Max. crimping diameter (mm)	6.0-89.0
Max. opening (without dies)	130mm
Max. crimping force (kN)	4075
Max. hose size	3/16" - 2" (6 wire)
Motor	220/240v 50hz single phase
Max. cycle time	10s closing, 10s opening